

TWO POST BASEPLATE LIFT

AMGO BP series baseplate two post lifts are stronger, safer, and easier to operate than most of the lifts in the world.



TWO POST LIFT

MAIN FEATURES

- √ 10,000 lbs capacity, chain-driven 2 post lift with baseplate. Able to lift heavy vehicles. Designed for low ceiling garages with overhead obstructions and decreased headroom.
- √ Single-point safety release allows the operator to unlock the safety locks from both columns simultaneously. There is also a dual locking system for additional safety.
- √ Super-symmetric arms provide versatility when choosing between asymmetric
 and symmetric positions and eliminates the need for two different kinds of lifts.

 The three-stage front arms and two-stage rear arms allows easy entry in and
 out of the vehicle when needed.
- \checkmark Automatic arm restraints keep the arms locked in their proper positions.
- \checkmark Self-lubricating UHMW Polyethylene sliders and bronze bushings.
- √ Aircraft quality cable used for synchronization.
- √ Detachable foot guard and tool tray to allow for a clutter free workspace.



Optional base plate, Kit No. 20903



The stackable rubber pads package with 1.5", 2.5", 5" extension adapters.



Single-point safety release makes it easier for operators to unlook both column locks from one location.





Two locks, one release.
Only available from AMGO.



Super symmetric arms designed with three-stage front arms and two-stage rear arms.

SPECIFICATIONS





Model		BP-10
Lifting Capacity		10,000lbs (4536kg)
Lifting Time		60S
Lifting Height	Α	77 3/8" ~ 86 3/8" (1965~2194mm)
Overall Height	В	111 7/8" (2841mm)
Overall Width	С	139 1/8" (3534mm)
Drive-Thru Clearance	D	100 3/4" (2560mm)
Width Between Columns	Е	112 1/4" (2850mm)
Minimum Pad Height	F	4 1/2" (115mm)
Motor		2.0HP
Gross Weight		1,693lbs (768kg)

AMGO HYDRAULIC CORPORATION

1931 Joe Rogers Jr Blvd, Manning, SC 29102, USA Tel: (803)505-6410 www.amgohyd.com

