

# DDEL 409-HP

AMGO 409-HP Pro series is built for full range vehicles including car, SUV and light truck. It boasts a lifting capacity at 9000lbs, can handle some tough works such as parking longer and taller vehicles. It's easy to install, requires barely maintenance and offers great mobility.

Safety Lock

Double safety locks provide

additional safety.

capacity: 9,000lbs.

TL certified power unit comes as standard.

ality cylinder is designed and made to a high standard.

s patented design concealed safety lock control device, with manual point lock release.

andard cables are included as standard.

- shaped columns are utilized to enhance strength.


p platforms come with foldable drive-in ramps as standard.


t back to back installation to minimize space occupancy.

side column can be installed at any corner.

ely high lifting is suitable to park taller vehicles.

e comes as standard.





### **IFICATIONS**

ing city	20000000	Α	В	С	C D		E		G	Н		1	J	K	Cross	
		Length	Outside edge of crossbeams	Overall Width	Width Between Posts	Max. Lifting Height	Max. locking height	Overall Height	Minmum Height	Max. Underneath Height	Max. Lock Underneath runway	Drive-Thru Clearance	Width Between Runways	Outside Edge of Runways	Gross Weight	Motor Power
Olbs	1435	238 1/8"	197 3/4"	119 1/8"	109 7/16*	87 11/16"	84 1/2*	96 5/8*	6 1/16"	82 15/16"	79 13/16"	98 1/4"	42 3/8"	82 3/8"		1.0HP,110V 2.0HP,220V
	575	75														2.0111-,2200

# **EXCLUSIVE FEATURES**



AMGO's patented design concealed safety lock control device, with manual single-point lock release.

Special structure design to allow back-to-back installation.

# **OPTIONAL PARTS**



Optional Caster Kits help easily maneuver the parking lift. One set 4pcs Kits No: 40801



Optional extended aluminum alloy drive-in ramps.G.W:20KGset, length:50" Kits No:40805



Optional Jack Tray Kit No.:40809



Optional Motor protect cover for outdoor installation Kits No.:40810.with emergency stop switch.



Optional plastic oil tray, Kits No.40807. Dimension: 42" x 23 5/8"



Optional J5H sliding jack with hand pump. 1.5" and 2.5" extension adapters included. Capacity 5,000lbs.

### AMGO HYDRAULIC CORPORATION

SC Division: 1931 Joe Rogers Jr Blvd, Manning, SC 29102, USA Tel:(803)505-6410

TX Division: 4310 Adler, Suite 200, Dallas, TX 75211, USA Tel:(214)377-7742

