



- 12000LBS(5500KG) LIFTING CAPACITY
- CE APPROVED AND CERTIFIED. IT HAS ADOPTED THE 115% DYNAMIC LOADING CAPACITY STANDARD AND WAS 150% STATIC LOADING CAPACITY TESTED
- MANUAL SAFETY RELEASE FROM TWO SIDES
- SYMMETRIC ARMS
- DUAL HYDRAULIC CHAIN-DRIVE CYLINDERS
- RUBBER PAD DOOR OPENING PROTECTION
- COMES WITH EXTENDED SUPPORT ADAPTOR SETS OF + 30 MM AND + 120 MM
- OVERHEAD SAFETY SHUTOFF BAR
- FEET-PROTECTION SAFETY GUARDRAILS WITH TOOLS BOX
- HIGH QUALITY HYDRAULIC SYSTEM WITH 220V/60HZ/1PH OR 110V/ 60HZ/ 1PH (OPTIONAL)

LIFTING CAPACITY	12000 LBS. (5500KG)
MAX. LIFTING HEIGHT	70.75" / 1800MM
MIN. HEIGHT	4.25" / 110MM
HEIGHT OVERALL	166.75" / 4235MM
WIDTH OVERALL	165.5" / 4204MM
OUTSIDE COLUMNS	151.25" / 3840MM
INSIDE COLUMNS	130" / 3390MM
DRIVE THRU CLEARANCE	117.75" / 2990MM
MOTOR	220VAC/60HZ/1PH
NET WEIGHT	1653LBS/750KG