

Shop Tools Outlet
 702 S 3rd Ave
 Marshalltown, IA 50158
 Phone: 888-288-6657
 Website: www.shoptooloutlet.com



Four Post Comparison Guide

Hy-Pro Brands

Ideal

	<u>FP-12</u>	<u>FP12K-K</u>	<u>FP-14K/A</u>	<u>FP14KC-X</u>	<u>FP14KAC-X</u>
Lift Model					
Capacity	12,000 lbs	12,000 lbs	14,000 lbs.	14,000 lbs.	14,000 lbs.
Alignment	No	No	A - Yes	No	Yes
2 Wheel Align/4 Wheel Align	N/A	N/A	152" - 167"	N/A	166 3/4" 103"-157"
Overall Length w/ Ramp	231 1/2"	N/A	208"	252 1/2"	252 1/2"
Overall Length w/o Ramps	205 3/4"	195"	N/A	208 1/2"	208 1/2"
Overall Width (Outside Base Plates)	129 1/2"	123"	N/A	142"	142"
Overall Height	83"	87"	N/A	92 1/2"	92 1/2"
Lifting Height	77 1/2"	67 1/2"	65 1/2"	77 1/2"	79 1/2"
Maximum Clearance under Track	70 3/4"	63 1/4"	N/A	69 5/8"	69 5/8"
Width Between Posts	114 3/8"	105"	108"	116 1/4"	116 1/4"
Length of Runways	191"	191 1/2"	N/A	196"	196"
Width of Runways	20"	19"	21 1/2"	20"	20"
Lifting Speed	75 seconds	N/A	N/A	N/A	N/A
Cable/Chain	Cable 1/2"	Cable	Chain	Cable	Cable
Lock Position	10	N/A	N/A	18	18
Power	3 HP 220V/1Ph	220V/1Ph	2HP 220V/1Ph 20Amps	220V 20Amp/1Ph	220V 20Amp/1Ph
Ship Weight	2638 lbs.	2,255 lbs.	2615 lbs. 3,305 lbs. 208x22x40 - FP-14K	2690 lbs.	3810 lbs.
Shipping Length	205"x25x30	194x24x40	212x24x36 + 208x23x30 -A	208x32x27	208x32x27
Minimum Recommended Bay Size				16' x 25'	16' x 25'

AMGO

	<u>Pro-12SX/ASX</u>	<u>Pro-12/A</u>	<u>Pro-14/A</u>	<u>Pro-14E/AE</u>
Lift Model				
Capacity	12,000 lbs.	12,000 lbs.	14,000 lbs.	14,000 lbs.
Alignment	ASX - Yes	A - Yes	A - Yes	AE - Yes
2 Wheel Align/4 Wheel Align	81 7/8"-157 1/2" 151 5/8"	78 3/4"-161 3/8" 155 7/8"	92 1/2"-175 1/4" 169 5/8"	92 1/2"-203 1/2" 169 5/8"
Overall Length w/ Ramp	232 5/8"	236 5/8"	257 1/2"	285"
Overall Length w/o Ramps	196 3/4"	200 3/4"	216 1/2"	245"
Overall Width (Outside Base Plates)	132 1/8"	126 1/4"	130 7/8"	130 7/8"
Overall Height	86"	86"	86"	86"
Lifting Height	73 1/2" 75 3/8"	73 1/2" 75 3/8"	73 1/2" 75 3/8"	73 1/2" 75 3/8"
Maximum Clearance under Track	66 7/8" 66 3/4"	66 7/8" 66 3/4"	65 5/8" 65 1/2"	65 5/8" 65 1/2"
Width Between Posts	118 1/8"	112 1/4"	116"	116"
Length of Runways	N/A	N/A	N/A	N/A
Width of Runways	20"	20"	20"	20"
Lifting Speed	45 seconds	63 seconds	76 seconds	76 seconds
Cable/Chain	Cable 1/2"	Cable 1/2"	N/A	
Lock Position				
Power	2.0 HP 220V/1Ph	2.0 HP 220V/1Ph	2.0 HP 220V/1Ph	2.0 HP 220V/1Ph
Ship Weight	2255 lbs. 2798 lbs.	2337 lbs 2791 lbs	2791 lbs. 3400 lbs	2945 lbs. 3576 lbs.
Shipping Length	200x23x29	204x23x29	218x23x31	247x23x31
Minimum Recommended Bay Size				